

PANEL ARMATÜRLER

CLOVE - SIVA ALTI



GÜÇ(watt)	15	20	40	40
IŞIK RENGİ	3000-4000-6500K			
IŞIK AKIŞI (LÜMEN)	1.500	2.000	4.000	4.000
VERİMLİLİK (LM/W)	100	100	100	100
ARMATÜR ÖLÇÜLERİ (mm)	295x295x35	295x595x35	295x1195x35	595x595x35
ÜRÜN AĞIRLIK (KG)	1	1,8	3,2	3,2



CLOVE - SIVA ÜSTÜ



GÜÇ(watt)	15	20	40	40
IŞIK RENGİ	3000-4000-6500K			
IŞIK AKIŞI (LÜMEN)	1.500	2.000	4.000	4.000
VERİMLİLİK (LM/W)	100	100	100	100
ARMATÜR ÖLÇÜLERİ (mm)	295x295x35	295x595x35	295x1195x35	595x595x35
ÜRÜN AĞIRLIK (KG)	1	1,8	3,2	3,2



FLOWER - SIVA ALTI



GÜÇ(watt)	15	20	40	40	70
IŞIK RENGİ	3000-4000-6500K				
IŞIK AKIŞI (LÜMEN)	1.650	2.200	4.800	4.800	8.400
VERİMLİLİK (LM/W)	110	110	120	120	120
ARMATÜR ÖLÇÜLERİ (mm)	295x295x70	295x595x70	295x1195x70	595x595x70	595x1195x70
ÜRÜN AĞIRLIK (KG)	1	1,8	3,2	3,2	5,8



FLOWER - SIVA ÜSTÜ



GÜÇ(watt)	15	20	40	40	70
IŞIK RENGİ	3000-4000-6500K				
IŞIK AKIŞI (LÜMEN)	1.650	2.200	4.800	4.800	8.400
VERİMLİLİK (LM/W)	110	110	120	120	120
ARMATÜR ÖLÇÜLERİ (mm)	300x300x70	300x600x70	300x1200x70	600x600x70	600x1200x70
ÜRÜN AĞIRLIK (KG)	1	1,8	3,2	3,2	5,8

