

## YOL VE SOKAK ARMATÜRLERİ

### LİON-S



GÜÇ(watt)	50	60	70	80
İŞIK RENGİ	3000-4000-6500K			
İŞIK AKIŞI ( LÜMEN)	6.500	7.800	9.100	9.600
VERİMLİLİK (LM/W)	130	130	130	120
ARMATÜR ÖLÇÜLERİ (mm)	281x388x92	281x388x92	281x388x92	281x388x92
ÜRÜN AĞIRLIK (KG)	3,4	3,4	3,4	3,4



### LİON-B



GÜÇ(watt)	100	120	130	140	150
İŞIK RENGİ	3000-4000-6500K				
İŞIK AKIŞI ( LÜMEN)	13.500	15.600	16.900	18.200	18.750
VERİMLİLİK (LM/W)	135	130	130	130	125
ARMATÜR ÖLÇÜLERİ (mm)	331x432x100	331x432x100	331x432x100	331x432x100	331x432x100
ÜRÜN AĞIRLIK (KG)	4,5	4,5	4,5	4,5	4,5



### LİNDEN



GÜÇ(watt)	60	80	100	120	140	160
İŞIK RENGİ	3000-4000-6500K					
İŞIK AKIŞI ( LÜMEN)	9.000	12.000	15.000	18.000	21.000	24.000
VERİMLİLİK (LM/W)	120	120	120	120	120	120
ARMATÜR ÖLÇÜLERİ (mm)	590x300x140			760x360x140		
ÜRÜN AĞIRLIK (KG)	5					

